



# Westerton UK Cutter Specifications

Westerton (UK) Limited

Model No:	2.75" WECT			3.625" RBCT	4.25" RBCT
Max Temp:	150°C (302°F) 200°C (392°F) with thermally shielded electronics			175°C (347°F) 200°C (392°F) with thermally shielded electronics	175°C (347°F) 200°C (392°F) with thermally shielded electronics
Max Pressure:	1,034 Bar (15,000psi)			1,511 Bar (22,000psi)	1,511 Bar (22,000psi)
Body OD:	2.75" (69.85mm)			3.625" (92.1mm)	4.25" (108mm)
Max well deviation:	Horizontal			Horizontal	Horizontal
Cable type:	Mono/Heptacable (Max 200Ω resistance)			Mono/Heptacable (Max 200Ω resistance)	Mono/Heptacable (Max 200Ω resistance)
Cutting Head diameter	2.75" (69.85mm)	3.00" (76.2mm)	3.25" (82.55mm)	3.625" (92.075mm)	4.25" (107.95mm)
Minimum recommended restriction:	3.00" (76.2mm)	3.25" (82.55mm)	3.50" (88.9mm)	3.875" (98.425mm)	4.50" (114.3mm)
Cutting range:	2.99"- 5.10" (75.946 – 129.54mm)	3.25"- 5.6" (85.55 – 142.24mm)	3.50"- 6.1" (88.9 – 154.94mm)	3.75"- 7.25" (95.25 – 184.15mm)	4.50"- 7.60" (114.3 - 193.04mm)
Max cut depth:	0.75" (19.05mm)	1.00 (25.4mm)		1.00" (25.4mm)	1.00" (25.4mm)
Anchor range:	2.99"- 5.00" (75.945 – 127mm)	3.10"- 5.00" (78.74 – 127mm)	3.50" -5.00" (88.9 – 127mm)	3.75"- 6.10" (95.25 – 154.94mm)	4.50"- 6.54" (114.3 – 166.12mm)
Material:	Carbon Steel L80 P110 S135 13% Cr	<b>Std. Head set-up:</b> Carbon Steel L80 P110 S135 13% Cr <b>Alt. Head set-up:</b> 25% Cr Inconel		Carbon Steel L80 P110 S135 13% Cr	Carbon Steel L80 P110 S135 13% Cr
Dimensions	2,849mm (112.2")			1,954mm (76.9")	2,139mm (84.2")
Weight	70.0Kg (154 lbs)			76.0 Kg (167.5 lbs)	108 Kg (238.1 lbs)